

DeLonghi



Eco - friendly refrigerant
NOW available



MAESTRO

ready to install air conditioners

***Perfect for the office, home, conservatory,
prefabricated buildings and park homes.***

*A unique proposition, a wall mounted air conditioner that is prepared
ready for installation. Just a few simple steps instantly give you a
comfortable air conditioned environment.*

*To create comfortable conditions all year
round De'Longhi's Maestro range is the
ideal solution.*

*Choose from cooling only, or cooling and
heat pump versions to suit your requirement.*

CF30AR/CP20AR

- CF30AR Cooling only
- CP20AR Cooling and Heat Pump
- Heat pump for cost effective background heating
- Stylish modern design
- Pre-charged refrigerant lines (4 metres) with quick coupling 'click clack' connectors
- Plugs into normal 13 amp electricity socket
- Infra red remote control
- Full auto mode, automatically changes operation mode to your requirements
- Programmable 24 hour timer
- Three fan speeds plus whisper quiet setting
- Autoswing louvres to vary direction of airflow



DeLonghi



MAESTRO *air conditioners*



Ready to install air conditioner



Quick easy coupling connection



Self sealing efficient lines

'Click clack' System

A cord 4 metres long, housing the refrigerant lines, connects the inside wall unit to the outside unit. Two 'click clack' couplings one male and one female located on the end of the cord and on the outside unit, simply snap together to complete the refrigerant circuit, and the electrical connections just push together. The Maestro is now ready for use.



Remote control

Technical specification	CF30AR	CP20AR	CP30AR	CP40AR
Voltage	220-240/1150 V-HZ	220-240/1150 V-HZ	220-240/1150 V-HZ	220-240/1150 V-HZ
Cooling capacity	11,500 Btu/h/3.4 kW	8000 Btu/h/2.3 kW	12,000 Btu/h/3.5 kW	17,050 Btu/h/5 kW
Heating capacity	-	2.4 kW	3.6 kW	5.4 kW
Power consumption	1150 W	760 W (heating)	1200 W (heating)	1760 W (heating)
Absorption current	5.4 A	3.9 A	5.5 A	8.1 A
Airflow rate (indoor cooling)	540 m ³ /hour	380 m ³ /hour	580 m ³ /hour	650 m ³ /hour
Dehumidification	1.6 litres/hour	1.2 litres/hour	1.8 litres/hour	2.2 litres/hour
Noise level Indoor unit	36 dB(A)	35 dB(A)	36 dB(A)	37 dB(A)
Outdoor unit	43 dB(A)	43 dB(A)	43 dB(A)	45 dB(A)
Electronic control	YES	YES	YES	YES
Programmable 24 hr timer	YES	YES	YES	YES
Auto mode function	YES	YES	YES	YES
Sleep function	YES	YES	YES	YES
Self diagnosis	YES	YES	YES	YES
Inter-connecting lines	4 metres	4 metres	4 metres	4 metres
Dimensions (h x w x d)				
Indoor unit	300 x 810 x 195 mm	270 x 750 x 175 mm	300 x 810 x 195 mm	300 x 967 x 195 mm
Outdoor unit	500 x 600 x 230 mm	500 x 600 x 230 mm	500 x 600 x 230 mm	640 x 800 x 280 mm
Refrigerant	R22/R290	R22/R290	R290	R290
Weight Indoor unit	9 kg	8 kg	9 kg	11 kg
Outdoor unit	35 kg	34 kg	35 kg	52 kg
Colour	Light grey	Light grey	Light grey	Light grey